



Chain	Pitch	Roller		Pin		Plate		Transverse Pitch (Pt)	Avg Uliitmate strength	Max Allowable Load	App.kg/m	
		Width (b1)	Dia (d1)	Dia (d2)	L	LC	h2					t/T
25-1	6.35	3.10	3.30	2.31	7.95	8.70	6.00	0.8	6.40	4.41	0.73	0.15
25-2					14.40	15.15				8.82	1.17	0.28
35-1	9.525	4.77	5.08	3.58	12.30	13.30	8.70	1.26	10.13	11.2	2.15	0.33
35-2					22.30	23.40				22.5	3.62	0.63
35-3					32.70	33.50				33.8	5.39	1.05
41-1	12.70	6.38	7.77	3.58	13.60	14.70	9.60	1.20	14.38	10.7	2.35	0.41
40-1	12.70	7.85	7.92	3.97	16.50	17.90	12.00	1.50	14.38	19.1	3.72	0.61
40-2					30.90	32.30				38.2	6.27	1.12
40-3					45.00	46.70				57.3	9.31	1.90
50-1	15.875	9.40	10.16	5.08	20.60	21.90	15.05	2.03	18.11	30.8	6.86	1.04
50-2					38.40	40.00				61.7	11.6	2.00
50-3					56.50	58.10				92.6	17.1	3.10
60-1	19.05	12.57	11.91	5.94	25.48	26.70	18.00	2.42	22.78	44.1	9.31	1.50
60-2					48.40	49.50				88.2	15.7	2.92
60-3					71.30	73.10				132	23.2	4.54
80-1	25.40	15.78	15.88	7.94	32.70	34.10	23.50	3.23	29.29	78.4	14.7	2.60
80-2					61.10	63.40				156	25.0	5.15
80-3					91.70	94.20				235	36.7	7.89
100-1	31.75	18.90	19.05	9.53	40.00	43.10	30.00	4.00	35.76	118	22.5	3.91
100-2					75.80	78.90				237	38.3	7.80
100-3					110.00	115.30				355	56.3	11.77
120-1	38.10	25.22	22.23	11.10	50.50	54.00	36.20	4.80	45.44	166	30.4	5.62
120-2					95.94	99.40				333	51.6	11.70
120-3					141.40	144.90				500	76.0	17.53

Chained to excellence, Geared for the future.