



Chain	Pitch	Roller		Pin			Plate		Avg. Tensile strength	Max Allowable Load	App.kg/m
		Width (b1)	Dia (d1)	Dia (d2)	L	LC	h2	T			
C2040	25.40	7.85	7.85	3.86	16.50	17.90	12.00	1.50	17.0	2.64	0.52
C2050	31.75	8.40	10.16	5.08	20.60	21.90	15.00	2.03	28.7	4.41	0.82
C2060	38.10	12.57	11.91	5.94	25.48	26.70	18.00	2.42	40.2	6.47	1.22
C2080	50.80	15.75	15.88	7.92	32.70	34.10	23.50	3.25	68.6	11.2	2.12
C2100	63.50	18.90	19.05	8.52	40.00	43.10	30.00	4.00	112	18.6	3.01
C2120	76.20	25.22	22.23	11.10	50.50	54.00	35.80	4.80	156	25.5	4.82
C2160	101.60	31.75	26.58	14.27	64.67	70.67	47.80	6.40	259	42.1	8.23
C2040H	25.40	7.65	7.95	3.96	18.80	19.90	12.00	2.03	17.0	2.64	0.62
C2050H	31.75	9.40	10.16	5.06	23.00	24.30	15.00	2.42	28.7	4.41	0.95
C2060H	38.10	12.57	11.91	5.94	29.20	31.60	18.00	3.25	40.2	6.47	1.45
C2080H	50.80	15.75	15.88	7.92	36.20	39.40	24.00	4.00	68.6	11.2	2.50
C2100H	63.50	16.90	19.05	9.52	43.60	46.90	30.00	4.60	112	18.6	3.84
C2120H	76.20	25.22	22.23	11.10	53.50	57.50	35.70	5.60	156	25.5	5.35
C2160H	101.60	31.75	28.58	14.27	86.20	73.00	47.60	7.20	259	42.1	9.06