



Chain	Pitch	Roller		Pin		Plate		Transverse Pitch (Pt)	Avg Ultimate strength	Max Allowable Load	App.kg/m	
		Width (b1)	Dia (d1)	Dia (d2)	L	LC	h2					t/T
04B	6.00	2.80	4.00	1.85	7.40	10.3	5.00	0.60	nil	3.00	nil	0.12
05B-1	8.00	3.00	5.00	2.31	7.95	11.70	7.10	0.80	nil	4.40	nil	0.16
05B-2					13.60	14.90			5.64	7.80	nil	0.33
06B-1	9.525	5.72	6.35	3.28	13.15	13.50	8.26	1.30	nil	9.00	1.7	0.41
06B-2					23.25	23.80			10.24	16.90	2.9	0.77
06B-3					33.80	34.00			10.24	24.90	4.2	1.16
08B-1	12.70	7.75	8.51	4.45	16.85	18.20	11.80	1.60	nil	17.80	3.14	0.69
08B-2					30.70	32.20			13.92	31.10	5.35	1.34
08B-3					44.80	46.00			13.92	44.50	7.85	2.03
10B-1	15.875	9.65	10.16	5.08	19.50	20.50	14.60	1.70	nil	22.20	4.9	0.94
10B-2					36.15	37.20			16.59	44.50	8.33	1.88
10B-3					52.80	53.80			16.59	66.70	12.2	2.81
12B-1	19.05	11.68	12.07	5.72	22.45	23.40	16.10	1.85	nil	29.00	7.06	1.21
12B-2					42.10	42.90			19.46	57.80	12	2.42
12B-3					61.60	62.30			19.46	86.70	17.6	3.43
16B-1	25.40	17.02	15.88	8.28	68.00	68.60	21.00	3.23/4.00	nil	60.00	12.6	2.77
16B-2					99.50	100.50			31.88	106.00	21.4	5.51
16B-3					131.00	132.40			31.88	160.00	31.5	8.25
20B-1	31.75	19.56	19.05	10.19	41.40	44.00	26.40	3.40/4.50	nil	95.00	19.6	3.90
20B-2					77.50	80.60			36.45	170.00	33.3	7.70
20B-3					114.00	116.90			36.45	250.00	49	11.53
24B-1	38.10	25.40	25.40	14.63	53.40	57.70	33.40	5.00/6.00	nil	160.00	27.5	6.79
24B-2					101.80	106.10			48.36	280.00	46.8	13.40
24B-3					150.20	154.40			48.36	425.00	64.1	20.00

Chained to excellence, Geared for the future.